

OKUMA

LT 200-MY

Stock no. :1022-2445

MACHINE-DATA

Machinetype : CNC Turning- and Milling Center
 Make : OKUMA
 Type : LT 200-MY
 Year : 2004.12
 Control type : CNC
 Control : Okuma OSP-E 100 L
 Storage location : Monheim (Germany)
 Origin : Japan
 Delivery time : Immediately
 Quotation : Ex warehouse, loaded on truck
 Price : on request



TECHNICAL DATA

turning diameter	210 mm
turning length	700 mm
control	Okuma OSP-E 100 L
total power requirement	35,7 kVA
weight of the machine ca.	7,1 t
dimensions of the machine ca.	2660 x 2000 x 2330* mm

TECHNICAL DESCRIPTION

CNC turning and milling center with C-axis and Y-axis, 2 turrets, and subspindle.

CNC control: Okuma OSP-E 100 L

Maximum turning diameter: 210 mm

Swing over bed: 400 mm

Distance between spindle noses: 960 mm

Main spindle:

Spindle bore: 53 mm



OKUMA

LT 200-MY

Stock no. :1022-2445

Speed range: 50 to 6000 rpm

Motor power: 11/7.5 kW

Subspindle:

Spindle nose: JIS A2-6

Speed range: 38 to 5000 rpm

Motor power: 11/7.5 kW

Z-axis:

Travel: 700 / 700 mm (ZA + ZB)

Rapid traverse: 40000 mm/min

W-axis:

Travel: 940 mm

Rapid traverse: 40000 mm/min

X-axis:

Travel: 167 / 192 mm (XA + XB)

Rapid traverse: 30000 mm/min

Y-axis:

Travel: 92 mm (+50/-42 mm)

Rapid traverse: 15000 mm/min

C-axis:

Indexing: 360 x 0.001 deg.

Rapid traverse: 400 rpm

Disc turret:

2 x 12 stations

Tool holder mount: VDI 30 mm

Power of driven tools: 4 kW

Total connected load: 35.7 kVA

Machine weight: 7100 kg

*Machine dimensions: 2660 x 2000 x 2330 mm**

Plus swarf conveyor and bar loader

Accessories

FMB Turbo 5-42/6200/A bar loader, year of manufacture 2005

Chip conveyor

Coolant system

Collet chuck for main and subspindle

Both turrets equipped with tool holders

Machine documentation.

CNC Turning- and Milling Center



OKUMA

LT 200-MY

Stock no. :1022-2445

VIDEO-LINKS

WEB-LINK



<http://mhp.logotech.de/hpm/v7/Datenblatt/datenblatt.php?machineno=1022-2445>



OKUMA

LT 200-MY

Stock no. :1022-2445



Technical details and information subject to amendments and errors.