

SATO

Satronik D4500

Stock no. :1022-E06337

MACHINE-DATA

Machinetype : Flame-Cutting Machine
Make : SATO
Type : Satronik D4500
Year : 2011/2008
Control type : CNC
Control : CNC 802
Storage location : Germany
Origin : Germany
Delivery time : Immediately
Quotation : Ex site, loaded on truck
Price : on request



TECHNICAL DATA

gangway length	14000 mm
working width	3700 mm
burner heads	6
Control	CNC 802

TECHNICAL DESCRIPTION

Used oxyfuel cutting machine with semi-automatic gas control and

6 oxyfuel torches

Working width 3700 mm

Track width 4500 mm

Overall width 5320 mm

Overall height 2100 mm

*Height above floor to bottom edge of torch support on track beam
mounted 1300 mm, floor-mounted without beam 1000 mm*

Track length 16000 mm on HE 300 B beam

Oxyfuel burner: 6 pieces with MS 832-250 blades



SATO

Satronik D4500

Stock no. :1022-E06337

Burner carriages: 6 pieces, maintenance arm mounted on round bar

Burner height adjustment: 6 pieces E 260 with 260 mm stroke

Maximum cutting thickness with 4 torches: 300 mm

Maximum cutting thickness with 6 torches: 200 mm

Feed speed: 12000 mm/min

CNC 802 control with vibration-resistant flash memory

Semi-automatic gas control via proportional valves

96 macros (modifiable standard shapes)

Easy to learn

USB interface

CNC Cut software for importing and converting DXF files

15" screen behind shatterproof, scratch-resistant glass, operable even with gloves.

Note:

A burner table and an extractor are not included in the scope of delivery.

VIDEO-LINKS

WEB-LINK

<http://mhp.logotech.de/hpm/v7/Datenblatt/datenblatt.php?machineno=1022-E06337>

Flame-Cutting Machine

SATO

Satronik D4500

Stock no. :1022-E06337



Brennschneidmaschine Sato D4500
mit Halbautomatischer
Gassteuerung und 6
Autogenbrenner

Technische Daten:

• Maschine Typ:	Satronik D4500
• Hersteller:	Sato
• Baujahr/Serie/Steuerung:	2011/2008
• Zustand:	gepflegt/neuwertig
• Angetriebentyp:	Gedrauchtmaschine
• Arbeitsbreite:	2700 mm
• Spurtiefe:	4500 mm
• Gesamtlänge:	15200 mm
• Gesamthöhe:	2100 mm
• Höhe über dem Boden bis unterste Brennersupport:	1300mm
• auf Lauffahrbahn montiert:	1000mm
• Laufrollenabstand:	16m auf Träger HE300B
• Energiequelle:	auf Wandanschluss gegen Aufpreis
• Autogenbrenner:	639k Messer MS832-250
• Brennerwagen:	639k Wartungsarm auf Rundstab gebogen
• Brennerhöhenverstellung:	639k E250 mit 250mm Hub
• Vorschubgeschwindigkeit:	12000mm/min
• Farbe:	RAL 5018/4005
• Anschlussspannung:	400V 50Hz 3N/PE
• Umgebungstemperatur:	+5° C - +40° C

• Steuerung: CNC802 mit Vibrationsentstörtem Flash Speicher
• Vollautomatische Gassteuerung über Proportionalventile
• 96 Module (Veränderbare Standardformate)

