AKYAPAK

SRP - 5

Stock no. :1022-E05047

MACHINE-DATA

Machinetype	: Rotary Welding Table - Round Surface
Make	: AKYAPAK
Type	: SRP - 5
Year	: Neu / New
Control type	: conventional
Control	:
Storage location	: Turkey
Origin	: Turkey
Delivery time	: approx. 8 - 10 weeks
Quotation	: ex manufacturer's works
Price	: on request

TECHNICAL DATA

table diameter	1525	mm
table load	5,0	t
swivelling range	0 - 100°	deg.
table rotating	360°	deg.
table turning speeds	0,05 - 1	U/min
table drive	1,5	kW
weight of the machine ca.	2,6	t
dimensions of the machine ca.	2295 x 1695	mm

TECHNICAL DESCRIPTION

Adjustable rotating speed
Remote controller with 5 meter cable length
Digital speed indicator on the controller panel for monitoring rotation
Welding – chassis mechanism
Mechanical angle indicator (for tilting movement)
Motors with brake & forced fan cooling
1 Year warranty

Technical details and information subject to amendments and errors.

AKYAPAK

SRP - 5

Stock no. :1022-E05047

VIDEO-LINKS

WEB-LINK

http://mhp.logotech.de/hpm/v7/Datenblatt/datenblatt.php?machineno=1022-E05047

Technical details and information subject to amendments and errors.

AKYAPAK

SRP - 5

Stock no. :1022-E05047

SRP - CONVENTIONAL POSITIONERS
AYARLI KAYNAK POZİSYONERİ



SRP
TECHNICAL SPECIFICATIONS / TEKNİK ÖZELLİKLER

S/N.	MODEL	Kapasite Yük - Capacity (kg) Ağırlık Merkezi - Centre of Gravity (kg)	Yükseklik Ayarı Aralığı Hareketsiz Uzaklık (mm) Height Adjustment Range (mm)	Plaka Üzerindeki Yükseklik (mm) Plate Surface Height (mm)	Eğme Dönebilme Açısı (°) Tilting Angle (°)	Güç Gücü (V) Input Power (V)	Eğme Motor Gücü (kW) Rotation Table Motor (kW)	Tilt Eğme Motoru (kW) Tilt Motor (kW)	Tabla Dönüş Hızı (RPM) Table Rotation Speed (RPM)		Eğme İmkanı (Ön-Orta) Tilting Capability (Front-Mid)	Tabla Çap (mm) Table Diameter (mm)	Bağlama Kanalları Sayısı - Açısı (°) Clamping Channels number - angle (°)	Yatay Dönüş Yüksekliği (mm) Horizontal Rotation Axis Height (mm)	Uzunluk (mm) Length (mm)	Yükseklik (mm) Height (mm)	Genişlik (mm) Width (mm)
			A	B					min	max		Ø		H	L	H	W	
1	SRP-015	150	100	100	90	380	0.18	0.25	04	25	30	500	5-72	700	800	950	700	600
2	SRP-05	500	100	100	135	380	0.25	0.25	0.17	0.58	30	700	6-60	803	1330	950	800	600
3	SRP-1	1000	150	150	135	380	0.55	0.55	0.18	1	30	920	6-60	845	1310	995	990	600
4	SRP-2	2000	150	150	135	380	0.75	0.75	0.05	1	45	1050	6-60	855	1500	1010	1210	600
5	SRP-3	3000	150	150	135	380	1.1	1.1	0.05	1	45	1220	6-60	1090	1600	1240	1300	600
6	SRP-5	5000	300	150	135	380	1.5	2.2	02	1	36	1525	6-60	1015	1800	1200	1540	600
7	SRP-10	10000	900	280	120	380	2.2	4.0	0.19	0.64	75	1830	6-60	1410	2032	2325	1885	600
8	SRP-15	15000	500	150	135	380	3	5.5	0.033	07	110	2200	6-60	1475	3200	1240	2200	600
9	SRP-20	20000	500	150	135	380	4	5.5	0.033	07	150	2400	6-60	1525	3300	1200	2450	600
10	SRP-25	25000	250	250	135	380	5.5	7.5	0.013	03	220	2940	12-30	1690	3800	1300	2940	800
11	SRP-40	40000	200	200	0	380	7.5	0	-	-	0	3500	8-45	-	3500	1680	3500	800

Technical details and information subject to amendments and errors.